

U.S. Patent Application Serial No. 09/830,232
 Reply to Office Action dated February 7, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1-8. (Cancelled)

9. (Currently Amended) A device for the reception of a multicarrier signal, formed by a set of carrier frequencies, said device implementing at least two reception paths supplied with data flows, each conveying a same source symbol ($x_k(n)$), each of said reception paths comprising ~~estimation means~~ an estimator associating with each source symbol received, an estimated path value and a corresponding confidence information element, wherein said source symbols are conveyed by a subset of said set of carrier frequencies, said device comprising means for ~~combination of~~ combining said estimated path values delivering:

an adapted estimated value, obtained from said estimated path values, in taking account of said path confidence information to weight said estimated path values; and

an adapted confidence information element, ~~and~~ said device further comprising:

a weighted-input decoding means decoder supplied by said adapted estimated value, wherein said means for ~~the combination~~ combining computes said adapted estimated value as follows:

$$\hat{x}_{Adap,n} = \left(\sum_{i=1}^N cnfd_{i,n} \times \hat{x}_{i,n} \right) / \left(\sum_{i=1}^N cnfd_{i,n} \right)$$

where:

$\hat{x}_{i,n}$ is the estimated value of the symbol received on the path i ;

$cnfd_{i,n}$ is the corresponding ~~path~~ confidence information element; and

U.S. Patent Application Serial No. 09/830,232
Reply to Office Action dated February 7, 2006

N is the number of paths.

10. (Currently Amended) A device for the reception of a multicarrier signal, formed by a set of carrier frequencies, said device implementing at least two reception paths supplied with data flows, each conveying a same source symbol ($x_k(n)$), each of said reception paths comprising ~~estimation means~~ an estimator associating with each source symbol received, an estimated path value and a corresponding confidence information element,

said source symbols being conveyed by a subset of said set of carrier frequencies,

said device comprising means for ~~combination of~~ combining said estimated path values delivering:

an adapted estimated value, obtained from said estimated path values, in taking account of said corresponding path confidence information to weight said estimated path values, and;

an adapted confidence information element, as a sum of said path confidence information elements, and said device further comprising:

a weighted-input decoding means decoder supplied by said adapted estimated value, wherein said means for ~~combination~~ combining computes said adapted confidence information element as follows:

$$cnfd_{Adap, n} = \sum_{i=1}^N cnfd_{i, n}$$

where:

$cnfd_{i, n}$ is the corresponding confidence information element associated with the path i ;
and

N is the number of *paths*.

11. (Previously Presented) A device for reception according to claim 9, wherein the reception device implements at least two antennas supplying distinct reception paths.

U.S. Patent Application Serial No. 09/830,232
Reply to Office Action dated February 7, 2006

12. (Currently Amended) A device for reception according to claim 9, wherein each of said reception paths comprises a first module shaping and demodulating the received signal and a second module determining said estimated path values and said corresponding confidence information elements, said device further comprising a single module supplied by said second module of each reception path, and providing for said means for ~~combination~~ combining said adapted estimated values and said weighted-input ~~decoding means~~ decoder supplied with said adapted estimated value.

13. (Previously Presented) A device for reception according to claim 10, wherein the reception device implements at least two antennas supplying distinct reception paths.

14. (Currently Amended) A device for reception according to claim 10, wherein each of said reception paths comprises a first module shaping and demodulating the received signal and a second module determining said estimated path values and said corresponding confidence information elements, said device further comprising a single module supplied by said second module of each reception path, and providing for said means for ~~combination~~ combining delivering said adapted estimated values and said weighted-input ~~decoding means~~ decoder supplied with said adapted estimated value.

15. (Currently Amended) A method for the reception of a multicarrier signal, ~~former~~ formed by a set of carrier frequencies transmitted simultaneously, implementing at least two reception paths supplied with data flows, each conveying the same source symbols, each of said paths implementing a step of ~~estimation of the~~ estimating of a transmission channel associating, with each source symbol received, an estimated path value and a corresponding path confidence information element a source symbol being conveyed by a subset of said set of carrier frequencies, said method comprising:

a combination step of delivering:

U.S. Patent Application Serial No. 09/830,232
 Reply to Office Action dated February 7, 2006

an adapted estimated value, obtained from said estimated path values in taking account of said corresponding path confidence information element to weight said estimated path values; and

an adapted confidence information element with each of said adapted estimated values, wherein said adapted estimated value is computed as follows:

$$\hat{x}_{Adap,n} = \left(\sum_{i=1}^N cnfd_{i,n} \times \hat{x}_{i,n} \right) / \left(\sum_{i=1}^N cnfd_{i,n} \right)$$

where:

$\hat{x}_{i,n}$ is the estimated value of the symbol received on the path i ,

$cnfd_{i,n}$ is the corresponding path confidence information element, and

N is the number of paths; and

a step of weighted-input decoding, ~~supplied by~~ taking into account said adapted estimated values.

16. (Currently Amended) A method for the reception of a multicarrier signal, ~~former~~ formed by a set of carrier frequencies transmitted simultaneously, implementing at least two reception paths supplied with data flows, each conveying the same source symbols, each of said paths implementing a step of ~~estimation of the~~ estimating of a transmission channel associating, with each source symbol received, an estimated path value and a corresponding path confidence information element, a source symbol being conveyed by a subset of said set of carrier frequencies, said method comprising:

combining and delivering:

an adapted estimated value, obtained from said estimated path values in taking account of said corresponding path confidence information element to weight said estimated path values, and

U.S. Patent Application Serial No. 09/830,232
Reply to Office Action dated February 7, 2006

an adapted confidence information element with each of said adapted estimated values, wherein said adapted confidence information element is computed as follows:

$$cnfd_{Adap,n} = \sum_{i=1}^N cnfd_{i,n}$$

where:

$cnfd_{i,n}$ is the corresponding confidence information element associated with the path i , and

N is the number of paths; and

weighted-input decoding, ~~supplied by~~ taking into account said adapted estimated values.